

Air Equipment— air supply

A 185 cfm compressor



B 375 cfm compressor



C Electric compressor #1776



D 3/8", 3/4" and 2" air hose



E Regulator, Moisture Separator, Fittings



F Air dryer



| Ref. | Description | CFM | PSI | Approx Gallons Per Hour | Weight | Day | Week | 4 Week |
|----------------------|--|------|---------|-------------------------|--------|-----|------|--------|
| A Compressors | | | | | | | | |
| | Portable Diesel Compressor | 185 | 115 | 2.8 | 2700# | 80 | 280 | 750 |
| | | 210 | 150 | 4.5 | 2700# | 120 | 300 | 850 |
| | | 300* | 150 | 4.5 | 5000# | 180 | 450 | 1150 |
| B | | 375* | 115/150 | 4.9 | 5200# | 235 | 590 | 1500 |
| | | 900 | 150 | 14.1 | 9800# | 510 | 1270 | 3245 |
| | | 1600 | 150 | 23.5 | 17000# | 910 | 2260 | 5700 |
| C | Electric- Ingersoll Rand 2HP- 20Gallon | 7.2 | 115 | 110V | 80# | 30 | 90 | 270 |
| | Electric- Bostitch TT150 | 4.1 | 90 | 110V | | 25 | 75 | 225 |
| | Electric- skid mounted | 25 | 125 | 220V | 300# | 65 | 190 | 490 |
| | | 175 | 125 | 600V | 1800# | 100 | 265 | 670 |
| | | 240 | 150 | 600V | 1980# | 145 | 345 | 880 |
| D | Air hose | | | | | | | |
| | 3/4" X 50' hose with Chicago ends and one whipcheck | | | | | 5 | 15 | 45 |
| | Short hose for dryer or separator, 3/4" x 5' or 3/4" x 10' | | | | | 3 | 6 | 12 |
| D | 2" X 50' hose, with swivel ends and one whipcheck | | | | | 10 | 40 | 120 |
| D | 3/8" X 50' hose, with quick couplers | | | | | 4 | 12 | 24 |
| E | Adapters | | | | | | | |
| | Dix-Lock adapter (DuPont), or spud to spud, or spud to pipe, or Chicago to pipe adapter or "Y" adapter | | | | | 3 | 6 | 12 |
| E | Filters | | | | | | | |
| | Moisture separator for 2" spud or 3/4" Chicago fitting | | | | | 15 | 60 | 180 |
| F | Air Dryer | | | | | | | |
| | Air dryer, 800 cfm. 2" spud or 3/4" Chicago | | | | | 25 | 60 | 160 |
| | Blow pipe | | | | | | | |
| | 4' blow pipe with ball valve | | | | | 5 | 10 | 15 |
| E | Whipcheck | | | | | | | |
| | 1/8" or 1/4" whipcheck | | | | | 2 | 4 | 8 |
| D | Air manifold | | | | | | | |
| | With 3/4" inlet and four 3/4" outlets with ball valve and 4 whipchecks | | | | | 15 | 60 | 120 |
| | Hitch adapter for Reese hitch to tow compressors- fits most trucks | | | | | 5 | 10 | 30 |
| * | Requires vehicle equipped with electric brake compatibility | | | | | | | |